

- EP-2501** With 14.4V Ni-MH Battery
- EP-2501C** With 14.4V Ni-MH Battery & Without Handle
- EPL-2501** With 14.4V Li-Ion Battery
- EPL-2501C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
300(L)x300(W)x78(H)mm  
Weight: 5.9kgs  
(Without Battery)

- EP-4201** With 14.4V Ni-MH Battery
- EP-4201C** With 14.4V Ni-MH Battery & Without Handle
- EPL-4201** With 14.4V Li-Ion Battery
- EPL-4201C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
430(L)x280(W)x75(H)mm  
Weight: 7.5kgs  
(Without Battery)

- EP-3001 & EP-4001** With 14.4V Ni-MH Battery
- EP-3001C & EP-4001C** With 14.4V Ni-MH Battery & Without Handle
- EPL-3001 & EPL-4001** With 14.4V Li-Ion Battery
- EPL-3001C & EPL-4001C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
400(L)x280(W)x70(H)mm (EP-3001)  
430(L)x270(W)x70(H)mm (EP-4001)  
Weight: 5.9kgs (EP-3001)  
Weight: 7.2kgs (EP-4001)  
(Without Battery)



General Specification	
Feature	360 degree swivel head
Application	Connector Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range
EP-2501 & EPL-2501 & EP-2501C & EPL-2501C	C-Jaw Opening 25mm
EP-3001 & EPL-3001 & EP-3001C & EPL-3001C	C-Jaw Opening 30mm
EP-4001 & EPL-4001 & EP-4001C & EPL-4001C	C-Jaw Opening 38mm
EP-4201 & EPL-4201 & EP-4201C & EPL-4201C	C-Jaw Opening 42mm
With Standard Dies 35 50 70 95 120 150 185 240 300 400 sqmm	

- EP-1501 & EP-2101** With 14.4V Ni-MH Battery
- EP-1501C & EP-2101C** With 14.4V Ni-MH Battery & Without Handle
- EPL-1501 & EPL-2101** With 14.4V Li-Ion Battery
- EPL-1501C & EPL-2101C** With 14.4V Li-Ion Battery & Without Handle



General Specification	
Feature	360 degree swivel head
Application	Non-insulated Terminal Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

Dimension:  
350(L)x240(W)x70(H)mm (EP-1501)  
350(L)x240(W)x70(H)mm (EP-2101)  
Weight: 6kgs (EP-1501)  
Weight: 6kgs (EP-2101)  
(Without Battery)

Model No.	Crimping Range
EP-1501 & EPL-1501 & EP-1501C & EPL-1501C	Max. 185mm <sup>2</sup>
With Male Dies(3pcs) 16-25/35-70/70-185 sqmm	
With Female Dies(1pc) 16/25-35/50-60/70-120/150-185 sqmm	
EP-2101 & EPL-2101 & EP-2101C & EPL-2101C	Max. 240mm <sup>2</sup>
With Male Dies(4pcs) 25-35/35-60/70-185/240 sqmm	
With Female Dies(1pc) 25-35/50-70/95-120/150-185/240 sqmm	

# 14.4V BATTERY CRIMPING TOOL

**EP-3251**  
**EP-3251C**  
**EPL-3251**  
**EPL-3251C**

With **14.4V Ni-MH Battery**  
 With **14.4V Ni-MH Battery & Without Handle**  
 With **14.4V Li-Ion Battery**  
 With **14.4V Li-Ion Battery & Without Handle**



Dimension:  
 400(L)x320(W)x80(H)mm  
 Weight: 5.6kgs  
 (Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Non-insulated Terminal Crimping
Output	18 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range
EP-3251 & EPL-3251 & EP-3251C & EPL-3251C	Max. 400mm <sup>2</sup>
With Male Dies(4pcs) 16/25-35/50-120/150-400 sqmm	
With Female Dies(1pc) 16-25/35-70/95-120/150-185/200/300/400 sqmm	

**EP-3501**  
**EP-3501C**  
**EPL-3501**  
**EPL-3501C**

With **14.4V Ni-MH Battery**  
 With **14.4V Ni-MH Battery & Without Handle**  
 With **14.4V Li-Ion Battery**  
 With **14.4V Li-Ion Battery & Without Handle**



Dimension:  
 390(L)x310(W)x70(H)mm  
 Weight: 5.6kgs  
 (Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Non-insulated Terminal Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range
EP-3501 & EPL-3501 & EP-3501C & EPL-3501C	35-400mm <sup>2</sup>
With Hexagon dies 35 50 70 95 120 150 185 240 300 400 sqmm	

**EP-4131**  
**EP-4131C**  
**EPL-4131**  
**EPL-4131C**

With **14.4V Ni-MH Battery**  
 With **14.4V Ni-MH Battery & Without Handle**  
 With **14.4V Li-Ion Battery**  
 With **14.4V Li-Ion Battery & Without Handle**



Dimension:  
 400(L)x280(W)x80(H)mm  
 Weight: 6.1kgs  
 (Without Battery)

General Specification	
Feature	360 degree swivel head
Application	CU & AL Connector Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah



Model No.	Crimping Range
EP-4131 & EPL-4131 & EP-4131C & EPL-4131C	Max. 400mm <sup>2</sup>
AR-413: DF & DM & LF Type Dies	
AR-415: Deep Indent dies 35-50/70-95sqmm	
AR-416: Deep Indent dies 120-150/185-240sqmm	

- EP-6301** With [14.4V Ni-MH Battery](#)
- EP-6301C** With [14.4V Ni-MH Battery](#) & Without [Handle](#)
- EPL-6301** With [14.4V Li-Ion Battery](#)
- EPL-6301C** With [14.4V Li-Ion Battery](#) & Without [Handle](#)



Dimension:  
420(L)x320(W)x75(H)mm  
Weight: 6.9kgs  
(Without Battery)

General Specification	
Feature	<a href="#">360 degree swivel head</a>
Application	CU & AL Connector Crimping
Output	18 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range
EP-6301 & EPL-6301 & EP-6301C & EPL-6301C	Max. 630mm <sup>2</sup>
With Standard Dies 35 50 70 95 120 150 185 240 300 400 500 630 sqmm	

- EDL-500** With [14.4V Ni-MH Battery](#)
- EDL-500C** With [14.4V Ni-MH Battery](#) & Without [Handle](#)
- EDLL-500** With [14.4V Li-Ion Battery](#)
- EDLL-500C** With [14.4V Li-Ion Battery](#) & Without [Handle](#)



Dimension:  
430(L)x78(W)x300(H)mm  
Weight: 7.6kgs

General Specification	
Feature	<a href="#">360 degree swivel head</a>
Application	CU & AL Connector Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range	
	DIN mm <sup>2</sup>	AWG/MCM
EDL-500 & EDLL-500 & EDL-500C & EDLL-500C	70-500	2/0-1000
Dieless Type		

# 14.4V BATTERY CRIMPING TOOL

- EP-6** With [14.4V Ni-MH Battery](#)
- EP-6C** With [14.4V Ni-MH Battery](#) & Without [Handle](#)
- EPL-6** With [14.4V Li-Ion Battery](#)
- EPL-6C** With [14.4V Li-Ion Battery](#) & Without [Handle](#)



Dimension:  
390(L)x310(W)x70(H)mm  
Weight: 4.8kgs  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Cable Lug Crimping
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range	
	DIN mm <sup>2</sup>	AWG/MCM
EP-6 & EPL-6 & EP-6C & EPL-6C	16-300	10-600
Dieless Type - Opening between Nibs: 32mm		

- EP-8** With [14.4V Ni-MH Battery](#)
- EP-8C** With [14.4V Ni-MH Battery](#) & Without [Handle](#)
- EPL-8** With [14.4V Li-Ion Battery](#)
- EPL-8C** With [14.4V Li-Ion Battery](#) & Without [Handle](#)



Dimension:  
420(L)x300(W)x70(H)mm  
Weight: 5kgs  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Cable Lug Crimping
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range	
	DIN mm <sup>2</sup>	AWG/MCM
EP-8 & EPL-8 & EP-8C & EPL-8C	25-400	3-750
Dieless Type - Opening between Nibs: 36mm		

- EP-22** With [14.4V Ni-MH Battery](#)
- EP-22C** With [14.4V Ni-MH Battery](#) & Without [Handle](#)
- EPL-22** With [14.4V Li-Ion Battery](#)
- EPL-22C** With [14.4V Li-Ion Battery](#) & Without [Handle](#)



Dimension:  
370(L)x290(W)x70(H)mm  
Weight: 4.3kgs  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Cable Lug Crimping
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range	
	DIN mm <sup>2</sup>	AWG/MCM
EP-22 & EPL-22 & EP-22C & EPL-22C	10-300	8-600
R22 Type <a href="#">Hexagon dies</a> - Please check the Dies-List		

- EP-58** With 14.4V Ni-MH Battery
- EP-58C** With 14.4V Ni-MH Battery & Without Handle
- EPL-58** With 14.4V Li-Ion Battery
- EPL-58C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
370(L)x290(W)x70(H)mm  
Weight: 3.9kgs  
(Without Battery)

General Specification	
Feature	180 degree Swivel Head
Application	Cable Lug Crimping
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range	
	DIN mm <sup>2</sup>	AWG/MCM
EP-58 & EPL-58 & EP-58C & EPL-58C	10-240	8-400
With Standard Dies 10-16/25-35/50-70/95-120/150-185/240 sqmm		

- EP-80** With 14.4V Ni-MH Battery
- EP-80C** With 14.4V Ni-MH Battery & Without Handle
- EPL-80** With 14.4V Li-Ion Battery
- EPL-80C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
390(L)x310(W)x70(H)mm  
Weight: 3.9kgs  
(Without Battery)

General Specification	
Feature	180 degree Swivel Head
Application	Cable Lug Crimping
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range	
	DIN mm <sup>2</sup>	AWG/MCM
EP-80 & EPL-80 & EP-80C & EPL-80C	10-300	8-600
With Standard Dies 10-16/25-35/50/70/95/120/150/185/240/300 sqmm		

- EP-185** With 14.4V Ni-MH Battery
- EP-185C** With 14.4V Ni-MH Battery & Without Handle
- EPL-185** With 14.4V Li-Ion Battery
- EPL-185C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
370(L)x280(W)x70(H)mm  
Weight: 3.8kgs  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Cable Lug Crimping
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range	
	DIN mm <sup>2</sup>	AWG/MCM
EP-185 & EPL-185 & EP-185C & EPL-185C	10-185	8-350
With Standard Dies 10-16/25-35/50-70/95-120/150-185 sqmm		

# 14.4V BATTERY CRIMPING TOOL

- EP-240** With 14.4V Ni-MH Battery
- EP-240C** With 14.4V Ni-MH Battery & Without Handle
- EPL-240** With 14.4V Li-Ion Battery
- EPL-240C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
390(L)x280(W)x70(H)mm  
Weight: 3.9kgs  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Cable Lug Crimping
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range	
	DIN mm <sup>2</sup>	AWG/MCM
EP-240 & EPL-240 & EP-240C & EPL-240C	10-240	8-400
With Standard Dies 10-16/25-35/50-70/95-120/150-185/240 sqmm		

- EP-150D & EP-210** With 14.4V Ni-MH Battery
- EPL-150D & EPL-210** With 14.4V Li-Ion Battery



Dimension:  
440(L)x230(W)x80(H)mm (EP-150D)  
440(L)x230(W)x80(H)mm (EP-210)  
Weight: 6.3kgs (EP-150D)  
Weight: 6.3kgs (EP-210)  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Non-insulated Terminal Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range
EP-150D & EPL-150D	Max. 185mm <sup>2</sup>
With Male Dies(3pcs) 16-25/35-70/70-185 sqmm	
With Female Dies(1pc) 16/25-35/50-60/70-120/150-185 sqmm	
EP-210 & EPL-210	Max. 240mm <sup>2</sup>
With Male Dies(4pcs) 25-35/35-60/70-185/240 sqmm	
With Female Dies(1pc) 25-35/50-70/95-120/150-185/240 sqmm	

- EP-250** With 14.4V Ni-MH Battery
- EPL-250** With 14.4V Li-Ion Battery



Dimension:  
420(L)x240(W)x75(H)mm  
Weight: 6.2kgs  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Connector Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range
EP-250 & EPL-250	C-Jaw Opening 25mm
With Standard Dies 35 50 70 95 120 150 185 240 300 400 sqmm	

**EP-300** With 14.4V Ni-MH Battery  
**EPL-300** With 14.4V Li-Ion Battery



Dimension:  
 440(L)x230(W)x75(H)mm  
 Weight: 6.3kgs  
 (Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Connector Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range
EP-300 & EPL-300	C-Jaw Opening 30mm
With Standard Dies 35 50 70 95 120 150 185 240 300 400 sqmm	

**EP-400 & EP-420** With 14.4V Ni-MH Battery  
**EPL-400 & EPL-420** With 14.4V Li-Ion Battery



Dimension:  
 470(L)x230(W)x80(H)mm (EP-400)  
 480(L)x240(W)x90(H)mm (EP-420)  
 Weight: 7.6kgs (EP-400)  
 Weight: 8.6kgs (EP-420)  
 (Without Battery)

General Specification	
Feature	360 degree swivel head
Application	Connector Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Crimping Range
EP-400 & EPL-400	C-Jaw Opening 38mm
EP-420 & EPL-420	C-Jaw Opening 42mm
With Standard Dies 35 50 70 95 120 150 185 240 300 400 sqmm	

**EP-413** With 14.4V Ni-MH Battery  
**EPL-413** With 14.4V Li-Ion Battery



Dimension:  
 450(L)x230(W)x75(H)mm  
 Weight: 6.4kgs  
 (Without Battery)

General Specification	
Feature	360 degree swivel head
Application	CU & AL Connector Crimping
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah



Model No.	Crimping Range
EP-413 & EPL-413	Max. 400mm <sup>2</sup>
AR-413: DF & DM & LF Type Dies	
AR-415: Deep Indent dies 35-50/70-95sqmm	
AR-416: Deep Indent dies 120-150/185-240sqmm	

# 14.4V BATTERY CABLE CUTTER

**EC-54** With 14.4V Ni-MH Battery  
**ECL-54** With 14.4V Li-Ion Battery



Dimension:  
 110(L)x100(W)x320(H)mm  
 Weight: 2.7kgs  
 (Without Battery)

General Specification	
Application	CU & AL Cable Cutting
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Cutting Range		
	DIN mm <sup>2</sup>	AWG/MCM	O.D.
EC-54 & ECL-54	500	750	52mm

**EC-55A** With 14.4V Ni-MH Battery  
**ECL-55A** With 14.4V Li-Ion Battery



Dimension:  
 190(L)x110(W)x330(H)mm  
 Weight: 3.2kgs  
 (Without Battery)

General Specification	
Application	ACSR Cutting
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Cutting Range	
	DIN mm <sup>2</sup>	O.D.
EC-55A & ECL-55A	120	18.6mm

**EC-95** With 14.4V Ni-MH Battery  
**ECL-95** With 14.4V Li-Ion Battery



Dimension:  
 240(L)x110(W)x350(H)mm  
 Weight: 3.1kgs  
 (Without Battery)

General Specification	
Application	CCP Cable Cutting
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Cutting Range
	O.D.
EC-95 & ECL-95	85mm

**EWR-34** With 14.4V Ni-MH Battery  
**EWRL-34** With 14.4V Li-Ion Battery



Dimension:  
 170(L)x110(W)x340(H)mm  
 Weight: 3.2kgs  
 (Without Battery)

General Specification	
Application	CU & AL Wire Cutting
Voltage	DC 14.4V
Capacity	3Ah

Model No.	Cutting Material	Cutting Range	
		DIN mm <sup>2</sup>	O.D.
EWR-34 EWRL-34	CU & AL Wire	250	

**EC-20** With 14.4V Ni-MH Battery  
**EC-20C** With 14.4V Ni-MH Battery & Without Handle  
**ECL-20** With 14.4V Li-Ion Battery  
**ECL-20C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
 320(L)x280(W)x70(H)mm  
 Weight: 3.7kgs  
 (Without Battery)

General Specification	
Feature	360 degree swivel head
Output	6 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.
EC-20 & ECL-20 EC-20C & ECL-20C
Cutting Range
<b>Wire Rope</b> 6×7: 16mm 6×12: 20mm 6×19: 20mm
<b>Soft Steel Bar</b> 20mm <b>Soft Rebar</b> 13mm <b>CU &amp; AL</b> 20mm

**EC-25** With 14.4V Ni-MH Battery  
**EC-25C** With 14.4V Ni-MH Battery & Without Handle  
**ECL-25** With 14.4V Li-Ion Battery  
**ECL-25C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
 385(L)x350(W)x70(H)mm  
 Weight: 4.7kgs  
 (Without Battery)

General Specification	
Feature	360 degree swivel head
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.
EC-25 & ECL-25 EC-25C & ECL-25C
Cutting Range
<b>Wire Rope</b> 6×7: 18mm 6×12: 25mm 6×19: 25mm
<b>Soft Steel Bar</b> 20mm <b>Soft Rebar</b> 15mm <b>CU &amp; AL</b> 25mm

# 14.4V BATTERY CABLE CUTTER

- EC-40** With 14.4V Ni-MH Battery
- EC-40C** With 14.4V Ni-MH Battery & Without Handle
- ECL-40** With 14.4V Li-Ion Battery
- ECL-40C** With 14.4V Li-Ion Battery & Without Handle

- EC-40A** *For ACSR Only*
- EC-40AC**
- ECL-40A**
- ECL-40AC**



Dimension:  
450(L)x295(W)x70(H)mm  
Weight: 5.4kgs  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.
EC-40 & ECL-40 EC-40C & ECL-40C
Cutting Range
<b>Wire Rope</b> 6×7: 22mm 6×12: 25mm 6×19: 25mm
<b>Soft Steel Bar</b> 20mm <b>Soft Rebar</b> 16mm <b>CU &amp; AL</b> 40mm
<b>Guy Wire</b> 1×7: 15mm 1×19: 20mm

- EC-32** With 14.4V Ni-MH Battery
- EC-32C** With 14.4V Ni-MH Battery & Without Handle
- ECL-32** With 14.4V Li-Ion Battery
- ECL-32C** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
410(L)x300(W)x70(H)mm  
Weight: 4.8kgs  
(Without Battery)

General Specification	
Feature	360 degree swivel head
Output	8 Tons
Voltage	DC 14.4V
Capacity	3Ah

Model No.
EC-32 & ECL-32 EC-32C & ECL-32C
Cutting Range
<b>CU</b> 32mm <b>AL</b> 28mm

- EC-85 & EC-85S** With 14.4V Ni-MH Battery
- EC-85C & EC-85SC** With 14.4V Ni-MH Battery & Without Handle
- ECL-85 & ECL-85S** With 14.4V Li-Ion Battery
- ECL-85C & ECL-85SC** With 14.4V Li-Ion Battery & Without Handle

General Specification	
Feature	360 degree swivel head
Output	6 Tons
Voltage	DC 14.4V
Capacity	3Ah



Dimension:  
580(L)x320(W)x70(H)mm  
Weight: 8.1kgs  
(Without Battery)

**EC-85**



**FLIP-TOP LATCH**  
*For easy insertion of cutting cable (EC-85S)*

**EC-85S**

Model No.
EC-85 & ECL-85 EC-85S & ECL-85S EC-85C & ECL-85C EC-85SC & ECL-85SC
Cutting Range
<b>CU</b> 46mm <b>AL</b> 28mm
<b>Telephone Cable</b> 85mm
<b>Underground Cable</b> 50mm
<b>Lead Sheathed Cable</b> 85mm

- EC-10** With [14.4V Ni-MH Battery](#)
- EC-10C** With [14.4V Ni-MH Battery](#) & Without [Handle](#)
- ECL-10** With [14.4V Li-Ion Battery](#)
- ECL-10C** With [14.4V Li-Ion Battery](#) & Without [Handle](#)



Dimension:  
280(L)x75(W)x310(H)mm  
Weight: 5.8kgs

General Specification		Model No.
Feature	360 degree swivel head	EC-10 & ECL-10 EC-10C & ECL-10C
Output	6 Tons	Cutting Range
Voltage	DC 14.4V	<b>Screw</b> Ø10mm
Capacity	3Ah	

- EC-13** With [14.4V Ni-MH Battery](#)
- EC-13C** With [14.4V Ni-MH Battery](#) & Without [Handle](#)
- ECL-13** With [14.4V Li-Ion Battery](#)
- ECL-13C** With [14.4V Li-Ion Battery](#) & Without [Handle](#)



Dimension:  
310(L)x280(W)x70(H)mm  
Weight: 4kgs  
(Without Battery)

General Specification		Model No.
Feature	360 degree swivel head	EC-13 & ECL-13 EC-13C & ECL-13C
Output	6 Tons	Cutting Range
Voltage	DC 14.4V	<b>Round Bar</b> Ø13mm
Capacity	3Ah	

- EC-20SR** With [14.4V Ni-MH Battery](#)
- EC-20SRC** With [14.4V Ni-MH Battery](#) & Without [Handle](#)
- ECL-20SR** With [14.4V Li-Ion Battery](#)
- ECL-20SRC** With [14.4V Li-Ion Battery](#) & Without [Handle](#)



Dimension:  
280(L)x75(W)x330(H)mm  
Weight: 9.2kgs

General Specification		Model No.
Feature	360 degree swivel head	EC-20SR & ECL-20SR EC-20SRC & ECL-20SRC
Output	18 Tons	Cutting Range
Voltage	DC 14.4V	<b>Alloy Chain 1/2"</b>
Capacity	3Ah	<b>Soft Steel Bar</b> Ø19mm
		<b>AL &amp; CU Rod 25mm</b>

# 14.4V BATTERY CABLE CUTTER

- EC-32WR** With 14.4V Ni-MH Battery
- EC-32WRC** With 14.4V Ni-MH Battery & Without Handle
- ECL-32WR** With 14.4V Li-Ion Battery
- ECL-32WRC** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
430(L)x310(W)x90(H)mm  
Weight: 8.4kgs  
(Without Battery)

Model No.
EC-32WR & ECL-32WR EC-32WRC & ECL-32WRC
Cutting Range
<b>Heavy Duty Steel Wire</b> Ø32mm

General Specification	
Feature	360 degree swivel head
Output	18 Tons
Voltage	DC 14.4V
Capacity	3Ah

- EC-52B** With 14.4V Ni-MH Battery
- EC-52BC** With 14.4V Ni-MH Battery & Without Handle
- ECL-52B** With 14.4V Li-Ion Battery
- ECL-52BC** With 14.4V Li-Ion Battery & Without Handle



Dimension:  
550(L)x300(W)x70(H)mm  
Weight: 7.6kgs  
(Without Battery)

- EC-52AB** *For ACSR Only*
- EC-52ABC**
- ECL-52AB**
- ECL-52ABC**

Model No.
EC-52B & ECL-52B EC-52BC & ECL-52BC
Cutting Range
<b>CU &amp; AL Telephone Cable</b> Ø52mm

General Specification	
Feature	360 degree swivel head
Output	10 Tons
Voltage	DC 14.4V
Capacity	3Ah

- EC-16** With 14.4V Ni-MH Battery
- ECL-16** With 14.4V Li-Ion Battery



Dimension:  
450(L)x240(W)x70(H)mm  
Weight: 6kgs

Model No.
EC-16 & ECL-16
Cutting Range
<b>Round Bar</b> Ø16mm

General Specification	
Feature	360 degree swivel head
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah

**EC-65Y & EC-85Y**  
**EC-65YC & EC-85YC**  
**ECL-65Y & ECL-85Y**  
**ECL-65YC & ECL-85YC**

With **14.4V Ni-MH Battery**  
 With **14.4V Ni-MH Battery** & Without **Handle**  
 With **14.4V Li-Ion Battery**  
 With **14.4V Li-Ion Battery** & Without **Handle**

Model No.	Application & Cutting Range	
	Suitable Material	Range
EC-65Y & ECL-65Y EC-85Y & ECL-85Y EC-65YC & ECL-65YC EC-85YC & ECL-85YC	Telephone CU/AL Cable(CCP)	O.D. 65/85mm
	Lead Sheathed Cable	O.D. 65/85mm
	Armored Underground Cable	O.D. 65/85mm

Warning: Do NOT cut any Rebar or Steel Wire or Big Strand or ACSR or Wire Rope



Dimension:  
 550(L)x310(W)x210(H)mm  
 Weight: 11.15kgs  
 (Without Battery)



**BLADE(EC65Y)**    **BLADE(EC85Y)**

General Specification	
Feature	360 degree Swivel Head
Output	12 Tons
Voltage	DC 14.4V
Capacity	3Ah