

ROTOFLUX - ROTARY UNIONS

**ROTO
FLUX**

Universal



S-Series
50 bar - 725 PSI
130°C - 265°F
3.500 RPM
1/4" ÷ 2"
Pass. 1 ÷ 2

Air and vacuum



T-Series
10 bar - 145 PSI (air)
6,7 Kpa - 28" Hg
(vacuum)
120°C - 245°F
3.500 RPM
1/8" ÷ 2"
Pass. 1

Stainless steel



F-Series
50 bar - 725 PSI
120°C - 245°F
3.500 RPM
1/4" ÷ 2"
Pass. 1 ÷ 2

High speed



A-Series
100 bar - 1.450 PSI
90°C - 195°F
15.000 RPM
1/4" ÷ 3/8"
Pass. 1
Yes for dry running

High pression



C-Series
400 bar - 5.800 PSI
90°C - 195°F
1.500 RPM
1/4" ÷ 3/4"
Pass. 1

High speed + air



B-Series
100 bar - 1.450 PSI
90°C - 195°F
20.000 RPM
1/4" ÷ 3/8"
Pass. 1
Yes for dry running

High speed + air



A-Series
10 bar - 145 PSI
90°C - 195°F
15.000 RPM
1/4" ÷ 3/8"
Pass. 1
Yes for dry running